

Graces series main parameters table

Step width		600		800			1000			
Inclination Degree		30°/35°								
Application scope		Indoor/outside door, 20 hours/per day								
Major parameters	Travel height	1500≤H≤21(30°)/1500≤H≤6000(35°)								
	Level step	H≤6m, 2level grade; H > 6m ,3level grade								
	Transport ability	3600		4800			6000			
	Rated	0.5m/s								
	Power supply	AC380V 50Hz; single ground wire								
	Light power	AC220V 50Hz								
Drive motor	Travel height	≤5000	≤6000	≤4000	≤5000	≤6000	≤3000	≤4500	≤6000	≤8000
	Motor power	5.5kW	8kW	5.5kW	8kW	11kW	5.5kW	8kW	11kW	15kW

* For specific parameters please refer to the drawings.

Escalator

Step width		600		800			1000			
Inclination degree		30°/35°								
Application		Indoor, able to operate 20 hours/day								
Main parameters	Travel height	1500≤H≤21(30°)/1500≤H≤6000(35°)								
	Level step	H≤6m, 2level grade; H > 6m,3level grade								
	Transport ability	3600		4800			6000			
	Rated speed	0.5m/s								
	Power supply	AC380V 50Hz; single ground wire								
	Light power	AC220V 50Hz								
Drive motor	Travel height	≤5000	≤6000	≤4000	≤5000	≤6000	≤3000	≤4500	≤6000	≤8000
	Motor power	5.5kW	8kW	5.5kW	8kW	11kW	5.5kW	8kW	11kW	15kW

* For specific parameters please refer to the drawings.