

T2 moving walk main parameters table

Inclination Degree		12°/11°/10°/6°/0°					
Application		Indoor, able to operate 16hours/day					
Basic parameters	Level length	L≤100000mm					
	Rated speed	0.5m/s					
	Power supply	AC380V 50Hz; single ground wire					
	Light power	AC220V 50Hz					
Drive motor	Step specification	800					
	Inclination degree	12°/11°/10°					
	Travel height	H≤2500	2500 < H≤4000	4000 < H≤5500	5500 < H≤7500	7500 < H≤8000	
	Motor powe	5.5kW	8kW	11kW	15kW	2*11kW	
	Step specification	1000					
	Inclination degree	12°/11°/10°					
	Travel height	H≤2500	2500 < H≤3500	3500 < H≤5000	5000 < H≤7000	7000 < H≤8000	
	Motor power	5.5kW	8kW	11kW	15kW	2*11kW	
	Step specification	800/1000					
	Inclination degree	6°					
	Travel height	H≤2000		2000 < H≤3000		3000 < H≤4000	
	Motor power	5.5kW		8kW		11kW	
	Step specification	800/1000					
	Inclination degree	0°					
	Level length	L≤100000mm					
	Motor power	5.5kW					

\* For specific parameters please refer to the drawings.

# Travelator

Inclination degree		12°/11°/10°/6°/0°				
Application		Indoor, able to operate 16hours/day				
Basic parameters	Level length	L≤100000mm				
	Rated speed	0.5m/s				
	Power supply	AC380V 50Hz; single ground wire				
	Light supply	AC220V 50Hz				
Drive motor	Step specification	800				
	Inclination degree	12°/11°/10°				
	Travel height	H≤2500	2500 < H≤4000	4000 < H≤5500	5500 < H≤7500	7500 < H≤8000
	Motor power	5.5kW	8kW	11kW	15kW	2*11kW
	Step specification	1000				
	Inclination degree	12°/11°/10°				
	Travel height	H≤2500	2500 < H≤3500	3500 < H≤5000	5000 < H≤7000	7000 < H≤8000
	Motor power	5.5kW	8kW	11kW	15kW	2*11kW
	Step specification	800/1000				
	Inclination degree	6°				
	Travel height	H≤2000		2000 < H≤3000		3000 < H≤4000
	Motor power	5.5kW		8kW		11kW
	Step specification	800/1000				
	Inclination degree	0°				
	Level length	L≤100000mm				
	Motor power	5.5kW				

\* For specific parameters please refer to the drawings.